

As tough as they get.

HSE EXTR@CORE® - frontier fibre cables breaking new ground.



A brand of the

Prysmian
Group

Frontier fibre cables breaking new ground.

Our latest test equipment brings trial and error to a completely new level, replicating forces only found in the most hostile black soil of Australia. The first result, HSE EXTRA@CORE®, was above all expectations. It's the toughest direct burial High Strength cable yet. Still it's small and lightweight and available in lengths up to 12 km. It all adds up in reduced installation costs, increased network reliability and reduced power loss. Australian made? Yes, of course!

HSE EXTRA@CORE®

Applications

HSE EXTRA@CORE® is Prysmian's Enhanced High Strength cable. It is specifically designed for direct burial in the most hostile black soil environments.

The toughest cable, yet

Using state of the art machinery and experienced technical knowledge Prysmian has further refined the High Strength cable design, making HSe the toughest cable yet.

A new and revealing test regime

HSe cable was qualified using Prysmian's newest and most revealing test regime - The Axial Compression Resistance (ACR) test. This next generation test equipment was designed in-house to specifically replicate forces exerted in reactive soil environments.

Easy to handle

HSe cable is small and light-weight, enabling easier handling in the field.

Available in longer lengths

HSe is now available in lengths up to 12 km. These longer lengths significantly reduce installation cost by maximising run lengths, increase network reliability and reduce power loss.



Prysmian - the sole supplier

As the sole supplier of High Strength cable to Australia's largest Telco's, including NBN and Telstra, Prysmian has unparalleled experience in the local market.

If you've got a tough installation that needs a tough cable, go for something with a bit eXTR@ - HSE EXTRA@CORE®.



eXTR@CORE

PRYSMIAN

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

