

CONSTRUCTION - PVC CABLES 0.6 /1kV

CONTROL 1.5MM² 2-50C+E SWA

PVC INSULATED LAID UP PVC BEDDED GSW ARMoured AND PVC SHEATHED CONTROL CABLE TO AS/NZS 5000.1.

For control circuits unenclosed, enclosed in conduit, buried direct or in underground ducts for commercial, industrial, mining and electricity authority systems where mechanical damage may occur. The 90°C cable is used where improved aging properties to those of 75°C PVC insulated cable are required because of higher ambient temperatures.



Cable Characteristics




Semi-rigid



12D



2


 Water
Splashes


Good


 +75 °C
-15 °C


C3



Good

Cable Design

CONDUCTOR:

Plain annealed copper conductor to AS/NZS 1125
Maximum continuous operating temperature: 75 °C

Can also be operated at temperatures up to 90 °C when not exposed to mechanical deformation (see AS/NZS 3008.1)

INSULATION:

V-90 PVC
Colours: White with Black numbering, Green/Yellow


ARMOUR:

Steel wire armour


SHEATH:

5V-90 PVC
Colours: Orange, Black


Installation Conditions


 INDUSTRIAL
EQUIPMENT




18D




IN FREE AIR




IN GROUND


 IN
CONDUIT



MACHINES



0 °C



IN TRENCH



IN DUCT

Physical & Electrical Characteristics

Product code	Cable									Min. installed bending radius mm
	Conductor nominal C.S.A. mm ²	Number of cores	Nominal insulation thickness mm	Diameter under armour		Armour wire diameter mm	Overall diameter		Approx. mass kg/100 m	
				Minimum mm	Maximum mm		Minimum mm	Maximum mm		
1.52CECONA	1.5	2	0.8	8.4	9.1	1.25	14.5	15.6	48	190
1.53CECONA	1.5	3	0.8	9.3	9.9	1.25	15.4	16.4	54	200
1.54CECONA	1.5	4	0.8	10.2	10.9	1.25	16.3	17.3	61	210
1.55CECONA	1.5	5	0.8	11.5	12.3	1.25	17.7	18.7	66	230
1.56CECONA	1.5	6	0.8	11.5	12.3	1.25	17.7	18.7	68	230
1.57CECONA	1.5	7	0.8	13.5	14.2	1.25	19.6	20.6	78	250
1.58CECONA	1.5	8	0.8	14.4	15.2	1.25	20.5	21.6	85	260
1.510CECONA	1.5	10	0.8	14.7	15.4	1.25	20.8	21.9	89	260
1.512CECONA	1.5	12	0.8	15.2	15.8	1.25	21.3	22.3	95	270
1.515CECONA	1.5	15	0.8	16.8	17.6	1.25	22.9	24.1	109	290
1.520CECONA	1.5	20	0.8	19.7	20.5	1.60	26.5	27.6	146	340
1.525CECONA	1.5	25	0.8	20.9	21.7	1.60	27.7	28.8	160	350
1.530CECONA	1.5	30	0.8	23.1	23.9	1.60	29.8	31.1	181	370
1.540CECONA	1.5	40	0.8	25.9	26.7	1.60	32.9	34.1	217	410
1.550CECONA	1.5	50	0.8	28.8	29.3	2.00	37.0	37.9	277	460

Number of cores	Current rating (a)			Electrical characteristics	
	Unenclosed spaced A	Buried direct A	Underground in duct A	Maximum D.C. resistance at 20°C Ω/km	Reactance per core Ω/km
2	19	28	22	13.6	0.111
3	16	24	19	13.6	0.111
4	16	24	19	13.6	0.111
5	14	24	14	13.6	0.111
6	13	22	13	13.6	0.111
7	13	22	13	13.6	0.111
8	12	21	12	13.6	0.111
10	11	19	11	13.6	0.111
12	11	18	11	13.6	0.111
15	10	17	10	13.6	0.111
20	9	15	9	13.6	0.111
25	8	14	8	13.6	0.111
30	8	13	8	13.6	0.111
40	7	12	7	13.6	0.111
50	7	12	7	13.6	0.111

(a) Based on 75 °C conductor temperature, 40 °C ambient air temperature and where applicable, burial depth of 0.5 m, soil temperature of 25 °C and soil thermal resistivity of 1.2 °C.m/W. Refer to AS/NZS 3008.1 for other installation conditions.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

Prysmian Australia Pty Ltd

1 Heathcote Road, Liverpool 2170 NSW, Australia
 Ph: 1300 300 304 Fax: 1300 300 307
 E-mail: sales.au@prysmiangroup.com

www.prysmiancable.com.au

