

COMMUNICATION CABLES – Telephone Cables

TELEPHONE EXTERNAL/CAT 3 M@XTEL®



Cable description:

Jelly Filled Category 3.

M@XTEL EXTERNAL/Cat 3 1/0.50 PACW, Polyethylene Insulated, Twisted Pair, Unit Construction.

Jelly filled, Core Wrapped, PE Sheathed. ACMA Approved.

Code	No. of pairs	Overall diameter mm	Min. bending radius mm	Max. pulling tension N	Mass kg/km
L25P30J	25	11.1	110	950	170
L50P30J	50	14.9	150	1900	320
L100P30J	100	20.2	200	3800	600

Guide for codes – Lan cable:

Product: L = Lan

Pair count: 4 = 4 pair, 25 = 25 pair etc

P: P = Pair

Category: 3 = Cat 3, 5E = Cat 5E, 6 = Cat 6, 6A = Cat 6A

Optional: O = Outdoor (Patch/Outdoor)

J = Jelly (Special materials)

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

Prysmian Cables & Systems Australia Pty Ltd

1 Heathcote Road, Liverpool 2170 NSW, Australia

Ph: 1300 300 304 Fx: 1300 300 307

E-mail: sales.au@prysmiangroup.com

www.prysmiancable.com.au

