


# SM@RTCORE® CT LITE

## External Underground Central Loosetube Optical Cable

**IEC 60794-3-11  
ACMA - AS/CA S008**

### Cable Design



- Drawing not to scale -

- **Central loose tube construction**

- **Tube:** Thermoplastic material, containing up to 12 optical fibres filled with a low viscosity, thixotropic, non-melting gel fully compatible with fibre coating and tube material
- **Peripheral strength members:** Water swellable aramid yarns
- **Longitudinal water tightness:** Water swellable elements (dry-core)
- **Sheath:** UV stabilised polyethylene in compliance with AS 1049.
- **Outer jacket:** UV stabilised polyamide (Nylon) in compliance with AS 1049 integrally bonded to PE sheath

This loose tube dielectric optical cable is designed for external underground installations in ducts by pulling, jetting or floating techniques.

### Technical data

<b>Number of Fibres</b>		<b>2 to 12</b>
Number of elements		1
Tube / Filler diameter	mm	2.4
Cable nominal diameter	mm	5.8
Cable nominal weight	kg/km	22
Max. installation tension	kN	1.0
Max. crush resistance	kN/100mm	2.0 (Short term) / 1.0 (Long term)
Min. bending radius	mm	At full load 150 At no load 80
Temperature range	°C	Installation -0 -> +50    Transport & Storage -20 -> +70    Operation -10 -> +70

### Optical Characteristics

See the attached cabled optical fibre data sheet.

### Identification

#### Fibre Colours

<b>No.</b>	1	2	3	4	5	6	7	8	9	10	11	12
<b>Colour</b>	blue	orange	green	brown	grey	white	red	black	yellow	violet	pink	aqua

#### Sheath Colour:

The outer sheath colour is light blue.

**Sheath Marking:**

The outer sheath is marked in 1 metre intervals as follows:

PRYSMIAN DW SM@RTCORE CT LITE Part Number T/N #### MM/YY MADE IN AUSTRALIA \*\*\*\*\*M

**Main mechanical characteristics**

Parameter	Test method	Test conditions	Acceptance criteria*
Tensile strength	IEC 60794-1-21-E1 Figure 2	Load: As per cable maximum tensile strength in table above.	After 30 minutes the maximum strain on the fibre should not exceed 0.6% and no attenuation increase occurs after test
Crush	IEC 60794-1-21-E3	Short time: 10 min Long time: 120 min Load: As per maximum crush resistance in table above Number of positions: 3 adjacent sections (ensuring one over tube and one over lay reversal)	No damage to the sheath or to the core structure and no attenuation increase occurs after test
Impact	IEC 60794-1-21-E4	Weight: 1.5 kg Height: 1.0 m Anvil radius: 300 mm Impacts: 3	After 5 minutes no fibre breaks, no damage to the sheath or to the core structure and no attenuation increase occurs after test
Torsion	IEC 60794-1-21-E7	Sample length: 1 m Rotation: a) 180° clockwise, b) return to starting position, c) 180° anticlockwise, d) return to starting position. Four movements constitute one cycle. Complete 10 cycles (a to d) in one minute maximum	During the final tenth cycle at a), c) and after completion (no rotation) check transmitting fibres. No fibre breaks, no damage to the sheath or to the core structure and no attenuation change throughout test
Bend	IEC 60794-1-21-E11	Mandrel radius: As per Min. bending radius at no load stated in technical data Bend: 360°, 5 turns, 3 cycles	No attenuation change throughout test
Bend under tension	Concurrent to tensile test IEC 60794-1-21-E18A	Mandrel radius: As per Min. bending radius at full load state in technical data Bend: 360°, 1turn	After 1minute no fibre breaks, no damage to the sheath or to the core structure and no attenuation change throughout test
Temperature cycling	IEC 60794-1-22-F1	Sample length: 1000 m (minimum) Temperature range: - 10 °C to +70 °C	There should be no average attenuation increase at the temperature extremes when compared to the attenuation at ambient temperature. No individual fibre should measure an attenuation greater than 0.15 dB/km
Water penetration	IEC 60794-1-22-F5B	Sample length=3m, Water height=1m	No water leakage after 24 hour

\* All optical measurements for singlemode fibres performed at 1550 nm.

**Logistic**

**Packing:**

Timber or plastic drums

**Delivery Lengths:**

Standard delivery length is 4 km with a tolerance of - 1% / + 3%  
Maximum delivery length is 10 km with a tolerance of - 1% / + 3%

© PrysmianGroup 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by PrysmianGroup.